RX8030 KIOTI Utility Tractor





Specifications

MODEL

ENGINE Make



ISO 9001 NO.954596

RX8030

Daedong

ISO 14001 NO.771475 NO:K033008 300Award Standard Equipment

World class


- · Front Weight (27kg x 10)
- · Sun Canopy
- Rear Remote Hydraulic Valve
- Rear PTO
- Draft Control
- 4WD
- Auto 4WD
- Rear View Mirror
- Parking Brake
- Battery
- Horn
- 7 Pin Socket
- · Rear Work Light
- Signal Lamp
- PTO Cover
- BOPS
- Suspension Type Deluxe Seat
- · Cup Holder
- Precleaner



High Projection Head and Working Lamp With the new projection head and working lamp, the operator will experience safe and easier operation in the dark operating conditions.



Hydraulic 4WD





The new SynchroShuttle on the RX Series provides smooth and easy shifting from forward to reverse. The transmission features 12 forward and 12 reversegears tohandleallkinds of jobs.

Make		Daedong
Model		4F243DTM-A
Туре		4Cyl., In-Line Vertical, Water-Cooled, Turbo Charge Diesel Engine
Engine Gross Power	HP(kw)	80 (59.69)
No, of Cylinders		4
Displacement	CC	2,435
Rated Revolution	rpm	2,600
Fuel Tank Capacity	Q	85
Engine Oil	Q	8.3
РТО		
Rated PTO Power	HP(kw)	71(53.69)
Rear PTO Type		Independent
Rear PTO Speed	rpm	540
DRIVE TRAIN		
Transmission		Synchro Shuttle Transmission
Speeds		12F x 12R
Differential Lock		Rear Standard
Steering		Hydrostatic Power Steering
Main Clutch Type		Dry Single Plate Clutch
Brake		Wet Multi Disc
Front Wheel Drive System		Hydro Multi Wet Disc Clutch
HYDRAULIC SYSTEM	1	
3 Point Lift Control Type		Position, Draft, Mixed Control
Implement Pump	lpm	41.6
Power Steering Pump	lpm	31.2
Total Hydraulic Flow	lpm	72.8
3 Point Hitch Type		Category II
Lift Capacity at Lift Point	kg.f	2.256
Drawbar Type		Drawbar
No. of Standard Remote Valves (Front/Rear)		(-/1)
TIRE SIZE		()))
AG Tire		Low Lug
Front		11.2-24
Rear		16.9-30
TRAVELING SPEEDS		10.0 00
Forward	km/h	1.51~35.07
Reverse	km/h	1.49~34.48
OTHERS	NINT	1.70-07.70
Tilt Steering		Std
One-Touch Hood Type		Std
Panel Type		Electric
DIMENSIONS		
Overall Length (W/O Front Weight and 3Pt Hitch)	mm	3,480
Overall Width (Minimum Tread)	mm	1,960
Tread Width - Front	mm	1,900
Tread Width - Rear	mm	1,475
Overall Height (ROPS) Wheel Base	mm	2,730
	mm	2,130
Ground Clearance	mm	440
Turning Radius (W/O Brake)	mm	3,930
Turning Radius (with Brake)	mm	3,370
Weight (with ROPS)	kg.f	2,535

*NOTE : Specifications and design are subject to change without notice



Agroscopio.com Lasso – Latacunga - Babahoyo Panamericana Sur KM 44 (matriz) +(593) 3 2700 203 +(593) 99 702 8131 www.tractorkioti.com www.agroscopio.com